

Shakers

SK-L330-Pro

SK-L180-Pro

LCD Digital Linear Shaker

Features:

- Max. load capacity is 7.5kg(L330) and 2.5kg(L180) with platform
- Double LCDs for independent display time and speed
- A wide range of platforms, accessories
- Maintenance- free brushless DC motor
- Over speed detection and protection



SK-L180-S

LED Digital Linear Shaker

Features:

- Max. load capacity is 3kg with platform
- Double LEDs for independent display of time and speed
- Speed range of 40-200 rpm
- Various of platforms accessories



SK-L180-E

Economical digital Linear Shaker

Features:

- Max. load capacity is 3kg with platform
- Speed range of 0-200 rpm
- Various of platforms accessories



Shakers



Timer



Wide range of accessories



Specifications

	SK-L330-Pro	SK-L180-Pro	SK-L180-S	SK-L180-E
Amplitude	10mm	4mm	20mm	20mm
Max. load capacity (with platform)	7.5kg	2.5kg	3kg	3kg
Motor type	Brushless DC motor	Brushless DC motor	DC motor	DC motor
Motor input power	28W	28W	16W	16W
Motor output power	15W	15W	10W	10W
Speed range	100-350rpm	100-350rpm	40-200rpm	0-200rpm
Speed display	LCD	LCD	LED	scale
Timer display	LCD	LCD	LED	-
Time settings range	1min-19h59min	1min-19h59min	1min-19h59min	-
Voltage	100-240V,50/60Hz	100-240V,50/60Hz	100-240V,50/60Hz	100-240V,50/60Hz
Power	30W	30W	20W	20W
Weight	13.5kg	8.1kg	3.1kg	3.1kg
Permissible ambient temperature and humidity	5-40°C, 80%	5-40°C, 80%	5-40°C, 80%	5-40°C, 80%
Dimensions[WxDxH]	370x420x100mm	300x340x100mm	270x330x110mm	270x330x110mm
Protection class	IP21	IP21	IP21	IP21
Data connector	RS232	RS232	-	-